SENSA[®] Flex

0000

Treatment chair for infusion and transfusion



SENSA[®] Flex

The chair with minimal space requirement and maximum comfort for your patients

SENSA® Flex A3 3 motors for adjustment of back-, foot- and seat part

SENSA® Flex A4 CA

4 motors for adjustment of back-, foot- and seat part and height adjustment plus central locking casters \oslash 10 cm

Hand switch A4 with buttons for basic settings (sitting, shock/ Trendelenburg position), magnetical locking function



tuv-sud.com/ps-cert

SENSA® Flex - minimal space requirement with maximum comfort for patients.

SENSA Flex has been developed for the specific needs in oncological day-care hospitals and the infusion and transfusion medicine and is additionally excellent qualified for the use in general medical practices. She only requires very little space – but at the same time offers high stability and safety against overturning and is also certified by TÜV. The therapy chair SENSA Flex convinces with stepless, motorized position adjustment. Easy entrance and exit from the chair's front is patient-friendly possible due to the low seat height and simplified through the advantageously foot part and the present seat inclination. Versatility and economic efficiency, the high patient comfort, with which even treatments lasting several hours can be undertaken in a relaxed manner, are characteristic for the SENSA Flex.

Features



Armrests incl. hand switch holder, rotatable, folding upwards and tiltable



Central locking casters \varnothing 10 cm (SENSA Flex A4 CA)



Upholstery (2-layer foam)



Entry and exit from the front



Individually locking casters \oslash 7.5 cm (SENSA Flex A3)



Entry and exit from the the side



Smooth surface: easy to clean and disinfect

- 3 motors for adjustment of back, foot and seat part (SENSA Flex A3)
- 4 motors for adjustment of back, foot and seat part and height adjustment (SENSA Flex A4 CA)
- Low wedge-shaped foam armrests right and left
- Armrests rotatable and folding upwards

- Armrests tiltable
- Individually locking casters Ø 7.5 cm (SENSA Flex A3)
- Upholstery (2-layer foam)
- Neck roll in upholstery colour
- Power rating 100–240 V AC, 50/60Hz
- EU power plug



Stepless motorized adjustment from seat-, comfort- and bed position to shock- or Trendelenburg position

Options



Paper roll holder



Push handle fixed



CPR release



Bag holder



Infusion rod holder right and left rotatable



Infusion rod incl. bottle holder



Relax pillow in upholstery colour



Tablet holder







Foam armrests of imitation leather incl. hand switch holder, right and left



USB charging port



Wedge-shaped foam armrests incl. hand switch holder, right and left



USB reading lamp for the USB charging port



Armrest with additional tilt adjustment



Upholstery wedge between seat- and backpart



Transparent, cleanable protactive cover for foot part and all armrests



Jersey stretch cover (washable) for upholstery, neck roll, relax pillow and all armrests



Pressure relieving gel seat cushion with PU-cover in grey



Antimicrobial upholstery



Lumbar support (in upholstery colour)



Upholstery 2-layer foam with special soft back- and seat part



Upholstery robust. The PU foam is particularly suitable for heavier patients.



Individually locking casters \varnothing 10 cm (SENSA Flex A3)



Equipotential bonding cable (absolutely necessary when using intracardiac procedures)



Individually locking casters with direction locking \oslash 10 cm (SENSA Flex A3)



Rechargeable battery



Grey holder with velcro. Made of grey imitation leather and suitable for foam armrest pads



Central locking casters \varnothing 10 cm (SENSA Flex A3)

Other power plug on request

Upholstery colours

| Standard c | olours | | | | | |
|-------------------|------------------------|-------|--------|-----------|----------|----------|
| ٩ | | ٩ | ٢ | ٩ | ۵ | |
| stone | saffron | kiwi | agave | azure | sapphire | |
| | | | | | | |
| | | | | | | |
| Additional | colours | | | | | |
| ۵ | | ٥ | | 6 | • | ٩ |
| cream | lemon | lime | purple | raspberry | red | chestnut |
| | ٩ | ٩ | | | | |
| chrome | anthracite | black | | | | |
| Also available as | antimicrobial upholste | ry. | | | | |

On neck roll and relax pillow the strap colour matches the colour of the upholstery.



DT 1 and ST 1

Side tables





Side table ST 1, fixed tray


incl. storage box

Side table DT 1, tiltable tray incl. storage box

Options



Flat, large tray, not removable, fixed to the frame (for ST 1)



Holder for monitor etc., ∅ 16 mm



Bottle holder/container



Lid for storage box, dark grey

HKL 1 and HVS 1 Universal stool



Universal stool HKL 1, foam seat part covered with imitation leather

Universal stool HVS 1, grey full foam (foamed) seat part

Features

- Single-handed, spring supported height adjustment
- Removable tabletop with finger-hollow
- Tiltable tray (only model DT 1)
- Detachable plastic storage box
- Holder, e.g. for bags
- Strong metal frame construction
- Plastic-coated subframe with excellent durability, protection against corrosion and abrasion

| Model | DT 1 and ST 1 |
|--------------------|-------------------------------|
| Height | 84 cm to 98 cm (adjustable) |
| Area required | 42 cm x 66 cm |
| Casters | Ø 5 cm |
| Storage box | 1 |
| Capacity | 6 l |
| Dimensions | approx. 17 cm x 27 cm x 15 cm |
| Colour | light grey RAL 7047 |
| Tray | 2 |
| Size | 40 cm x 53 cm (removable) |
| Small, trapezoidal | 40/30 cm x 18 cm (fixed) |
| Colour | light grey RAL 7047 |
| Colour of frame | light grey RAL 7047 |
| Maximum load | 25 kg |
| Weight | 17 kg |
| | |

Features

- Base with easy ring control
- Continuous height adjustment via gas spring
- Mobile "soft brake" with wheels for hard floors (for example laminate, parquet)
- Standard colour of seat part universal stool (for HKL 1) see colour chart

Options

■ Special colour for seat part (only HKL 1)

| Model | HVS 1 | HKL 1 | |
|---------------------|-----------------------------|------------------|--|
| Height | 53 cm to 71 cm (adjustable) | | |
| Area required | 56 cm x 56 cm | | |
| Casters | Ø 5 cm | | |
| Seatpart | Ø 38 cm (shore 15° A) | | |
| Colour of seat part | grey | see colour chart | |
| Weight | 7 kg | | |

Subject to technical alterations, improvements and errors.

Technical Specifications



| Technical data | SENSA Flex A3 SENSA Flex A4 | CA |
|--|--------------------------------|------|
| Armrests length x width | 51.5 cm x 15.5 cm | |
| Upholstery length x width x height | 198.7 cm x 53.5 cm x 7.0 cm | |
| Total length (max.) x width | 198.7 cm x 84.4 cm | |
| Seating height | 57 cm to 78 cm | |
| Angle of inclination | | |
| Back part | 0° to 81° (Shoulder area) | |
| | -20° to 61° (Loin area) | |
| Seat part | 7° to 20° | |
| Foot part | -77° to 20° | |
| in Shock, Trendelenburg position | 20° | |
| Upholstery material | UV-proof, impermeable to moist | ure, |
| | checked for biocompatibility | |
| | and toxicity, flame retardant | |
| Colour covers and metal frame | light grey RAL 7047 | |
| Colour upholstery | refer to the colour chart | |
| Colour armrest refer to the colour chart | | |
| Casters | | |
| Individually locking Ø 7.5 cm | - | |
| Individually locking $arnothing$ 10 cm | - | |
| Central locking Ø 10 cm | | |
| Motorised adjustment of | | |
| Back part | | |
| Seat part | | |
| Foot part | | |
| Height adjustment | | |

| Technical data | SENSA® Flex A3 SENSA® Flex A4 CA |
|-----------------------------------|----------------------------------|
| Battery | |
| Equipotential bonding | |
| Power rating, primary | 100–240 V AC, 50/60 Hz |
| Power rating, secondary | 29 V |
| Fuses | Internal |
| Protection type hand control unit | IP 66 |
| Protection type controller | IP X4 |
| Protection class | |
| Duty cycle | 2 min ON/18 min OFF |
| Consumption in standby | approx. 1 W |
| El. equipment | DIN FN 60601-1 |
| FMC. | DIN EN 60601-1-2 |
| Spiral power cable | 2.0 m to 3.5 m |
| Permitted air pressure | 800 to 1060 hPA |
| Ambient temperature | 10° to 40° C |
| Emission sound pressure level | < 65 dB(A) |
| Medical device class | I |
| Applied parts type | - B |
| Safe working load | 200 kg |
| Weight (without options) | 60 kg 75 kg |
| Guarantee | 2 years |
| Guarantee | 2 years |

= Standard 🛛 = Option



Made in Germany



LiKAMED is certified

- QM certification according to EN ISO 13485 tuv-sud.com/ps-cert
- Certified environmental management system according to EN ISO 14001 tuv-sud.com/ms-cert



LiKAMED GmbH · Raußmühlstraße 7 · 75031 Eppingen · Germany Phone: +49 7262 9189-0 · E-mail: info@likamed.de www.likamed.de